GP25K GENERATOR

21KVA DIESEL GENERATOR RENTAL



AUSTRALIAN DESIGNED

FUEL EFFICIENT

CUSTOMISABLE

DURABLE

Powered by Kubota

PRODUCT SPECIFICATIONS

GENERAL

Model	GP25K
Power Type	Diesel
Prime Power (kW/kVA)	17/21
Standby Power (kW/kVA)	18.7/23.1
Rated Current	29.5AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Kubota V2003T-E2BG
Aspiration	Turbocharged
No. of Cylinders	4
Governor Type	Mechanical governor
Lubricating Oil Capacity	7.6L

ALTERNATOR

Model	GP184E1
Frequency	50
Rate Power (kW/kVA)	18/22.5
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±0.5%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	2100 x 1000 x 1280
Dry Weight	1300 kg

FUEL CONSUMPTION

Fuel Consumption*	4.3(L/h)
Fuel Tank Capacity	160L

NOISE LEVEL

Sound Pressure at 7m/dB	64

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating - Outlets 2x32Amp 3Φ, 2x15Amp 1Φ
Fully bunded extended run fuel tanks

WARRANTY

12 months or 1200 Hours, subject to Ts & Cs

OPTIONS

Remote Monitoring

*Fuel consumption based on 75% load

GP-GP25K-V3-0625

Disclaimer: Specifications are indicative only and may vary between model years or individual units. For equipment hire, we will supply the same or an equivalent model that is fit for the disclosed purpose.