ACCESS HIRE AUSTRALIA

HIRE | SALES | SERVICE | LEASE | TRANSPORT

GP28FWS-1 GENERATOR

25KVA DIESEL GENERATOR STANDBY



AUSTRALIAN DESIGNED

FUEL EFFICIENT

CUSTOMISABLE

DURABLE

Powered by FAWDE

PRODUCT SPECIFICATIONS

GENERAL

Model	GP28FWS-1
Power Type	Diesel
Prime Power (kW/kVA)	25/25
Standby Power (kW/kVA)	25/25
Rated Current	104AMPS
Operating Ambient Temp.	50°C
Voltage output	240V

ENGINE

Engine Model	Fawde 4DX21-45D
Aspiration	Natural
No. of Cylinders	4
Governor Type	Electrical
Lubricating Oil Capacity	7.5L

ALTERNATOR

Model	GP184F1
Frequency	50
Rate Power (kW/kVA)	22/22
Power Factor	1
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±1.0%
No. of Phases	1
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	2240 x 1100 x 1290
Dry Weight	1140kg

FUEL CONSUMPTION

Fuel Consumption*	5.8(L/h)
Fuel Tank Capacity	100L

NOISE LEVEL

Sound Pressure at 7m/dB 64

SAFETY FEATURES

ISO Compliant
Emergency E Stop
Fitted with ATS
Remote stop start option

CONTROL SYSTEM

Operator friendly DSE control system 6120

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
Fully bunded extended run fuel tanks
3 way extended fuel connections

WARRANTY

12 months warranty, subject to Ts & Cs

*Fuel consumption based on 75% load

GP-GP28FWS-1-V1-0725

Disclaimer: Specifications are indicative only and may vary between model years or individual units. For equipment hire, we will supply the same or an equivalent model that is fit for the disclosed purpose.