

## RT4069 SCISSOR LIFT

### 40FT DIESEL SCISSOR LIFT WIDE DECK

#### Performance

|                                                 |               |          |
|-------------------------------------------------|---------------|----------|
| Platform Height—Elevated                        |               |          |
| RT2669                                          | 26'2"         | 8 m      |
| RT3369                                          | 32'8"         | 10 m     |
| RT4069                                          | 40'3"         | 12.3 m   |
| RT4769                                          | 47'           | 14.3 m   |
| Platform Height — Lowered                       |               |          |
| RT2669                                          | 4'3"          | 1.3 m    |
| RT3369                                          | 4'9"          | 1.5 m    |
| RT4069                                          | 4'10"         | 1.5 m    |
| RT4769                                          | 5'4"          | 1.6 m    |
| Platform Capacity (Single Extension)            |               |          |
| RT2669                                          | 1,500 lb      | 680 kg   |
| RT3369                                          | 1,000 lb      | 454 kg   |
| RT4069                                          | 800 lb        | 363 kg   |
| RT4769                                          | 800 lb        | 363 kg   |
| — Capacity on Deck Extension                    | 300 lb        | 136 kg   |
| No. Occupants (Indoor/Outdoor)                  |               |          |
| RT2669                                          | 4/4           |          |
| RT3369                                          | 4/2           |          |
| RT4069                                          | 3/2           |          |
| RT4769                                          | 3/2           |          |
| Lift/Lower Time                                 |               |          |
| RT2669                                          | 36/28 seconds |          |
| RT3369                                          | 42/33 seconds |          |
| RT4069                                          | 69/46 seconds |          |
| RT4769                                          | 81/55 seconds |          |
| Maximum Drive Height                            |               |          |
|                                                 | Full Height   |          |
| Weight (single extension w/out leveling jacks)* |               |          |
| RT2669                                          | 8,058 lb      | 3,655 kg |
| RT3369                                          | 8,856 lb      | 4,017 kg |
| RT4069                                          | 10,536 lb     | 4,779 kg |
| RT4769                                          | 13,635 lb     | 6,185 kg |
| Drive Speed—Lowered                             | 3.5 mph       | 5.6 km/h |
| Drive Speed—Elevated                            | 0.5 mph       | 0.8 km/h |
| Max Tilt Rating (side-to-side)                  | 2.5 Degrees   |          |
| Max Tilt Rating (fore & aft)                    | 3 Degrees     |          |
| Gradeability                                    |               |          |
| RT2669                                          | 40%           |          |
| RT3369                                          | 40%           |          |
| RT4069                                          | 35%           |          |
| RT4769                                          | 30%           |          |
| Turning Radius (Inside)                         | 83"           | 2 m      |
| Turning Radius (Outside)                        | 175"          | 4 m      |

\* Certain options or country standards will increase weight.

#### Standard Specifications

##### Tires

|           |                     |
|-----------|---------------------|
| Tire Size | 26 x 12 Foam Filled |
|-----------|---------------------|

##### Engine

|                    |                                    |
|--------------------|------------------------------------|
| Dual Fuel Engine   | Kubota WG972-GL-E4 31 hp (23.2 kw) |
| Diesel Engine      | Kubota D1805-E4B 24.8 hp (18.5 kw) |
| Fuel Tank Capacity | 10 gal (38L)                       |

##### Drive

4WD Hydrostatic

##### Hydraulic System

|                     |                 |
|---------------------|-----------------|
| Hydraulic Reservoir | 13.2 gal (50 L) |
|---------------------|-----------------|



#### Standard Features

- 42in Roll-out Deck Extension
- Nickel Plated Pins, Yellow Zinc-Chromate Plated Fasteners
- Pin-Less Fold Down Rail System
- Platform Control Box with LCD Display, USB Charger and Phone Holster
- Self-Closing Gate
- Full Time Traction Control
- Lubrication-Free Scissor Arm Bushings
- Manual Descent Pull Cable
- Oscillating Front Axle
- Scissor Maintenance Prop
- Tie Down Lugs
- 26 x 12 Foam Filled Lug Tread Tires
- 110V-AC Receptacle In Platform
- All Motion Alarm
- Horn
- Hourmeter
- Proportional Lift and Drive
- Pin-based Load Sensing System
- Telematics-Ready Harness
- LCD Display with LiftSense System
- Fold Down Rails
- ECU Controlled Engine Speed
- Remote Engine Oil Filter Package
- ANSI A92.20 Compliant

#### Accessories & Options

- 33.5 lb Aluminum Propane Tank
- Moveable, Removable Platform Control Box
- Hydraulic Leveling Jacks (Auto Level)
- Hydraulic Oil Cooler (Excludes RT4069)
- 26 x 12 Foam Filled Non-Marking Tires
- Flashing Amber Beacon - LED
- Dual Flashing Amber Beacons - LED
- White Noise Backup Alarm
- Special Hydraulic Fluids
- Special Paint
- ClearSky™
- Operator Access Control
- 2500W Generator 60Hz/110V (Belt-driven)
- Dual LP Tanks (Dual Fuel Engines only)
- QuikLevel Advanced
- Heavy Duty Pipe Racks
- 2WD

1. RT4769 Includes a Push-Button Manual Descent System

## RT4069 SCISSOR LIFT

40FT DIESEL SCISSOR LIFT WIDE DECK

### Dimensions

All dimensions are approximate.



#### Platform Height — Elevated

|        |       |        |
|--------|-------|--------|
| RT2669 | 26'2" | 7.98 m |
| RT3369 | 32'8" | 9.96 m |
| RT4069 | 40'3" | 14.1 m |
| RT4769 | 47'   | 14.3 m |

#### A. Platform Height — Lowered

|        |       |        |
|--------|-------|--------|
| RT2669 | 4'3"  | 1.3 m  |
| RT3369 | 4'9"  | 1.46 m |
| RT4069 | 4'10" | 1.46 m |
| RT4769 | 5'4"  | 1.62 m |

#### B. Platform Railing Height\*

|        |       |        |
|--------|-------|--------|
| RT2669 | 44.7" | 1.14 m |
| RT3369 | 44.7" | 1.14 m |
| RT4069 | 44.7" | 1.14 m |
| RT4769 | 44.7" | 1.14 m |

\*Fold Down Rails

#### C. Overall Height

|        |        |        |
|--------|--------|--------|
| RT2669 | 96.7"  | 2.46 m |
| RT3369 | 102.9" | 2.61 m |
| RT4069 | 103"   | 2.62 m |
| RT4769 | 109.1" | 2.77 m |

#### D. Platform Dimensions

130.5" x 63" 3.3 x 1.6 m

#### E. Platform Extension

42" 1.07 m

#### F. Overall Machine Length

139" 3.53 m

#### G. Overall Machine Width

69.3" 1.76 m

#### H. Wheelbase

81.3" 2.07 m

#### I. Ground Clearance

10.1" 25.7 cm