


GP30K GENERATOR

27.5KVA DIESEL GENERATOR RENTAL

AUSTRALIAN
DESIGNED

FUEL EFFICIENT



CUSTOMISABLE



DURABLE

Powered by
Kubota

PRODUCT SPECIFICATIONS

GENERAL

Model	GP30K
Power Type	Diesel
Prime Power (kW/kVA)	20/25
Standby Power (kW/kVA)	22/28
Rated Current	35AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Kubota V3300-E2BG2
Aspiration	Natural
No. of Cylinders	4
Governor Type	Mechanical Governor
Lubricating Oil Capacity	13.2L

ALTERNATOR

Model	SLG184F1
Frequency	50
Rate Power (kW/kVA)	22/27.5
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±1.0%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	2300 x 1000 x 1570
Dry Weight	1290 kg

FUEL CONSUMPTION

Fuel Consumption*	7.6(L/h)
Fuel Tank Capacity	210L

NOISE LEVEL

Sound Pressure at 7m/dB	70
-------------------------	----

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating- Outlets 2x15 Amp 1Φ, 2x32 Amp 3Φ
Fully bunded extended run fuel tanks

WARRANTY

12 months or 1200 Hours, subject to Ts & Cs

OPTIONS

Remote Monitoring

*Fuel consumption based on 75% load

GP-GP30K-V3-0625