

SL2012-E SCISSOR LIFT

65FT ELECTRIC SCISSOR LIFT NARROW

Size	Metric	British
Max. Working Height A	22.00m	72ft 2in
Max. Platform Height B	20.00m	65ft 7in
Overall Length C	4.72m	15ft 6in
Overall Width D	1.25m	4ft 1in
Overall Height(Rails Up) E	3.82m	12ft 6in
Overall Height(Rails Down) F	2.99m	9ft 10in
Platform Size(Length×Width)	4.30m×1.19m	14ft 1in × 3ft 11in
Platform Extension Size G	1.80m	5ft 11in
Ground Clearance(Stowed/Raised)	0.20m/0.02m	8in/1in
Wheelbase H	3.18m	10ft 5in
Turning Radius(Inside/Outside)	1.6m/2.3m	5ft 3in/7ft 7in
Tyres	28×10-22	28×10-22

Performance		
S.W.L	750kg	1653lb
S.W.L On Extension	750kg	1653lb
Max. Occupants	2	2
Gradeability	25%	25%
Travel Speed(Stowed)	3.0km/h	3.0km/h
Travel Speed(Raised)	0.5km/h	0.5km/h
Max. Working Slope	1°(0°)	1°(0°)
Up/Down Speed	85/75sec	85/75sec

Weight		
Overall Weight	12350kg	27227lb

Power		
Hydraulic Tank	130L	130L
Battery	48V/630Ah	48V/630Ah
Charger	48V/60A	48V/60A
Driving Motor	4×AC 32V/3.3kW	4×AC 32V/3.3kW
Lifting Motor	2×DC 48V/8.0kW	2×DC 48V/8.0kW

* The platform height plus 2m (7ft in British standard) is the working height.
Standards Compliance

