GP220C GENERATOR

200KVA DIESEL GENERATOR RENTAL



AUSTRALIAN DESIGNED

FUEL EFFICIENT

CUSTOMISABLE

DURABLE

Powered by Cummins

PRODUCT SPECIFICATIONS

GENERAL

Model	GP220C
Power Type	Diesel
Prime Power (kW/kVA)	160/200
Standby Power (kW/kVA)	176/220
Rated Current	278 AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Cummins 6CTAA8.3G2
Aspiration	Turbo-charged and air to air aftercooled
No. of Cylinders	6
Governor Type	Electronic governor
Lubricating Oil Capacity	23.8L

ALTERNATOR

Model	GP274H1
Frequency	50
Rate Power (kW/kVA)	160/200
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±0.5%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	3800 x 1400 x 2100
Dry Weight	3550 kg

FUEL CONSUMPTION

Fuel Consumption*	34 (L/h)
Fuel Tank Capacity	1080L

NOISE LEVEL

Sound Pressure at 7m/dB 74

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating - Outlets 2x15 Amp 1Φ 2x32 Amp 3Φ 1x63 Amp 3Φ
Fully bunded extended run fuel tanks

WARRANTY

12 months or 1200 Hours, subject to Ts & Cs

OPTIONS

3 way fuel valves - Standard
Multiple synchronization of units - Special Build
Load share capabilities - Special Build

*Fuel consumption based on 75% load

GP-GP220C-V4-1125

Disclaimer: Specifications are indicative only and may vary between model years or individual units. For equipment hire, we will supply the same or an equivalent model that is fit for the disclosed purpose.