

TF35.7-100 TELEHANDLER

3.5T DIESEL TELEHANDLER INDUSTRIAL (7.0M)

	PERFORMANCE AND FEATURES	TF35.7-100 EE	TF33.9-100 EE	
	PERFORMANCE			
	Total unladen weight (kg)	6600	6900	
	Maximum capacity (kg)	3500	3300	
	Lifting height (m)	6,6	8,6	
	Maximum reach (m)	3,6	5,8	
	Maximum operating height (m)	6,1	6,1	
	Maximum operating reach (m)	1,3	1,5	
	Capacity at maximum height (kg)	3000	1750	
	Capacity at maximum reach (kg)	1250	550	
	Lateral boom movement (mm)	-	-	
	Tilting correction (%)	-	-	
	Boom sections	2	3	
	POWERTRAIN			
	Turbo motor	Kubota V3800	Kubota V3800	
	Displacement/cylinders	3800/4	3800/4	
	Engine Power (kW/HP)	74/100	74/100	
	Anti-pollution technology	TIER 3, STAGE IIIA	TIER 3, STAGE IIIA	
	Reversible fan	●	●	
	Maximum speed (km/h)	40	40	
	Fuel tank (l)	80	80	
	AdBlue tank (l)	-	-	
	Hydrostatic transmission	● - 2V	● - 2V	
	EPD	-	-	
	Axles	Axial	Axial	
	Reduction hub	Epicyclic	Epicyclic	
	Machine brakes	Dry discs	Dry discs	
	Automatic parking brake	●	●	
	HYDRAULIC			
	Hydraulic pump	LS+FS	LS+FS	
	Flow rate/pressure (l/min - bar)	140-210	140-210	
	Hydraulic tank	85	85	
	Hydraulic outlet at the top of the boom	●	●	
	Rear hydraulic outlets	○	○	
	CAB			
	Cab configuration	ECO	ECO	
	MCDC	Complet	Complet	
	FOPS LII cab	●	●	
	ROPS cab	●	●	
	Cab commands	Electronic joystick	Electronic joystick	
	Tilting Cab	-	-	
	Reverse shuttle	Dual reverse	Dual reverse	
	CONFIGURATION			
	Cab suspension	-	-	
	Boom suspension	●	●	
	Suspension on axles	-	-	
	Work headlights on cab	●	●	
	Sun blind	●	●	
	Tac-lock	●	●	
	Provision for a platform	○	○	
	Two floating forks	●	●	
	Inching-Control	●	●	
	Four-wheel drive	●	●	
	Four-wheel steering	●	●	
	Three steering modes	●	●	
	Standard tyres	405/70-24	405/70-24"	
	Optional tyres	-	-	
	Stabilisers	-	-	
	Turner rotation	-	-	
	Type approval as an agricultural tractor	-	-	
	Approval with PNEUMATIC braking	-	-	
	Approval with HYDRAULIC braking	-	-	
	PTO	-	-	
	3-point linkage	-	-	

- Not Available. ● standard. ○ optional.