GP10K GENERATOR

10KVA DIESEL GENERATOR RENTAL



AUSTRALIAN DESIGNED

FUEL EFFICIENT

CUSTOMISABLE

DURABLE

PRODUCT SPECIFICATIONS

GENERAL

Model	GP10K
Power Type	Diesel
Prime Power (kW/kVA)	8/10
Standby Power (kW/kVA)	8.8/11
Rated Current	41.6AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Kubota D722
Aspiration	Natural
No. of Cylinders	3
Governor Type	Mechanical Governor
Lubricating Oil Capacity	3.8L

ALTERNATOR

Model	Stamford GP042D
Frequency	50
Rate Power (kW/kVA)	10
Power Factor	0.8
Exciter Type	Brushless
Voltage Regulator	AS440
Voltage Regulation	1.0%
No. of Phases	Single
Insulation	Class H
Protection	GP23
Altitude	1000m

UNIT

Dimensions (LxWxH)	1365 x 1113 x 760
Dry Weight	575kg

FUEL CONSUMPTION

Fuel Consumption*	2.5(L/h)
Fuel Tank Capacity	60L

NOISE LEVEL

Sound Pressure at 7m/dB	64

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE6020 control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating - 1x32 AMP 3 Φ, 2x15 Amp 1Φ
Fully bunded extended run fuel tanks

WARRANTY

12 months or 1200 Hours, subject to Ts & Cs

OPTIONS

3 way fuel valves
Remote Monitoring

*Fuel consumption based on 75% load

GP-GP10K-V4-0426

Disclaimer: Specifications are indicative only and may vary between model years or individual units. For equipment hire, we will supply the same or an equivalent model that is fit for the disclosed purpose.