

T MANUAL PALLET JACK

☎ 13 4000

P2.0 WAREHOUSE EQUIPMENT

T MANUAL PALLET JACK

ERGONOMICS	P2.0S	P2.5S	P3.0S
Key switch start	STD	STD	STD
Tiller control - fixed height*	STD	STD	STD
Tiller control - adjusted height*	X	X	X
Scooter control for models with side and rear protections	STD	STD	STD
Intelligent Lift™	X	X	X
Soft lowering	X	X	X
Coasting function	X	X	X
CONSTRUCTION	P2.0S	P2.5S	P3.0S
Standard construction	STD	STD	STD
Cold store construction (-30° C)	X	X	X
Standard platform with side arms	STD	STD	STD
Standard platform without side arms	X	X	X
Foot sensor for models with side protection	X	X	X
Platform with rear protection plate (via special order)	X	X	X
Platform with side protection plates	X	X	X
LIFT	P2.0S	P2.5S	P3.0S
Without load backrest	STD	STD	STD
1800mm high load backrest	X	X	X
1180 x 552 X-1005mm forks	STD	STD	STD
Other dimension forks	X	X	X
Fork height from ground - 85mm	STD	STD	STD
Fork height from ground - 75mm	X	N/A	N/A
Adjustable tie rod	X	N/A	N/A
OPERATION	P2.0S	P2.5S	P3.0S
Standard travel speed 13Km/h (with speed reduction on cornering)	STD	STD	STD
Audible forward alarm (forks trailing)	X	X	X
Audible reverse alarm (forks leading)	X	X	X
Audible forward and reverse alarm	X	X	X
Pedestrian awareness light (P.A.L.)	X	X	X
254 x 90mm NDilthane® drive wheel	STD	STD	STD
254 x 90mm NDilthane® conductive drive wheel	X	X	X
254 x 90mm DynaRoll® drive wheel	X	X	X
254 x 90mm Redthane® drive wheel	X	N/A	N/A
85 x 90mm tandem NDilthane® load wheels	STD	STD	STD
85 x 114mm single NDilthane® load wheels	X	N/A	N/A
75 x 90mm tandem NDilthane® load wheels	X	N/A	N/A
75 x 114mm single NDilthane® load wheels	X	N/A	N/A
Multifunctional display	STD	STD	STD
12V DC/DC converter	X	X	X
24V DC/DC converter	X	X	X
A4 clip board	X	X	X
Bottle holder	X	X	X
Multipurpose bar - across	X	X	X
Hyster Tracker Wireless Monitoring	X	X	X
Hyster Tracker Wireless Access	X	X	X
Hyster Tracker Wireless Verification	X	X	X
Manual work light	X	X	X
Automated work light	X	X	X
Premium platform lights	X	X	X

BATTERIES	P2.0S	P2.5S	P3.0S
Hyster standard type battery	X	X	X
Hyster battery with aquamatic	X	X	X
Hyster battery with aquamatic and air mix	X	X	X
Side extraction (using rollers)	STD	STD	STD
624 x 212 x 627mm battery compartment (for 210/250 Ah DIN Battery)	X	N/A	N/A
624 x 284 x 627mm battery compartment (for 315/375 Ah DIN Battery)	STD	STD	STD
624 x 356 x 627mm battery compartment (for 500Ah DIN Battery)	X	X	X
Battery cable extension (1500mm)	X	X	X
Twin battery charge station	X	X	X
Gravity feed water reservoir	X	X	X
On board charger with UK plug	X	X	X
On board charger with Schuko plug	X	X	X
On board charger with CH plug	X	X	X
SUPPLEMENTAL	P2.0S	P2.5S	P3.0S
Literature pack	X	X	X
CE certification	STD	STD	STD
24 months / 4,000 hours manufacturer's warranty	STD	STD	STD
36 months / 6,000 hours extended warranty	X	X	X

* Available for Foldable Platform models only.
Please refer to the Price List for full option configurations.
Contact Hyster for details.