


Z60/34 BOOM LIFT

60FT DIESEL BOOM LIFT ARTICULATED



MODEL	Z™-60/34	
MEASUREMENTS	Metric	US
Working height maximum*	20.39m	66 ft 4 in
Platform height maximum	18.39m	60 ft 4 in
Horizontal reach maximum	11.05m	36 ft 3 in
Up and over clearance maximum	8.23m	27 ft
A Platform length	0.91m	3 ft
B Platform width	2.44m	8 ft
C Height - stowed	2.69m	8 ft 10 in
D Length - stowed	8.15m	26 ft 9 in
E Width	2.46m	8 ft 1 in
F Wheelbase	2.51m	8 ft 3 in
G Ground clearance - centre	0.41m	1 ft 4 in

PRODUCTIVITY		
Lift capacity	227kg	500 lbs
Platform rotation	180°	180°
Vertical jib rotation	90°	90°
Turntable rotation	360° continuous	
Turntable tailswing	zero	zero
Drive speed - stowed	4.8 km/h	3.0 mph
Drive speed - raised**	1.1 km/h	0.68 mph
Gradeability - 4WD - stowed***	40%	40%
Turning radius - inside	3.04 m	10 ft
Turning radius - outside	6.07 m	19 ft 11 in
Controls	12 V DC proportional	
Tyres - RT Lug - Foam filled	385/65 D19.5	

POWER		
Power source	Deutz D2011L03i 3-cylinder diesel 35.8 kW (48 hp)	
Auxiliary power unit	12 V DC	12 V DC
Hydraulic tank capacity	170.3 L	45 gal
Fuel tank capacity	75.7 L	20 gal

WEIGHT****		
	11,800 kg	26,014 lbs

STANDARDS COMPLIANCE	ANSI A92.5, CSA B354.4, CE Compliance, AS 1418.10
----------------------	---

* The metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft to platform height.
 ** In lift mode (platform raised), the machine is designed to operate on firm, level surfaces only.
 *** Gradeability applies to driving on slopes. See operators manual for details regarding slope ratings.
 **** Weight will vary depending on options and/or country standards.

RANGE OF MOTION Z™-60/34

