HAC20K-20 GENERATOR

15KVA HYBRID GENERATOR HYBRID AC

Globe Power's Lithium Iron Phosphate Hybrid AC units provide a reduction of diesel consumption and are low emission, assisting in reducing carbon footprint and hitting green energy emission targets.

Suitable for a high load start up and low running power demands, the all in one system is both efficient in power and cost.

AUSTRALIAN DESIGNED | SMART FEATURES & LATEST TECHNOLOGIES | DURABLE & COST EFFECTIVE | EASY TO TRANSPORT

Powered By: SOLAR TECH GROUP





PRODUCT SPECIFICATIONS

GENERAL

Model	HAC20K-20 v1.2
Voltage	230V AC 50Hz
Output Power	15kVA Continuous Load, Standby Peak 25kVA (1hr)

BATTERY

Battery Type	51.2V Lithium Iron Phosphate
Battery Capacity	20.5kWh
Recharge Time	3 hours (10-100%)

OPERATIONAL DATA

Operating Temperature	0°C - 50°C
Altitude	0 - 1500m
IP Rating	IP54
Input	15A 3 pin Grid Charging
Output	2x10A, 1x15A, 2x32A, 1x63A, 3x400A quick connects

UNIT

Dimensions (LxWxH)	2090 x 1050 x 2185mm
Weight (WET)	1800kg
Engine	Yanmar 4TNV88 - Tier 5
Cooling	Air- conditioned enclosure
Fire Prevention	4.5kg ABC Extinguisher & Battery Fire Suppression Modules

FUEL CONSUMPTION

Fuel Consumption (L/h)	3.6L @ 75% load
Fuel Tank Capacity (L)	173L - 110% Bunded includes 3 way fuel valves

NOISE LEVEL

Sound Pressure	71db @ 7m

SOLAR INPUT

Voltage	250V DC Max
Power	2 x 4kW Charge Controllers Suits 4 Solar Skids

GP-HAC20K-20-V3-0525

Disclaimer: Specifications are indicative only and may vary between model years or individual units. For equipment hire, we will supply the same or an equivalent model that is fit for the disclosed purpose.