

JCPT1212AC SCISSOR LIFT

38FT ELECTRIC SCISSOR LIFT WIDE DECK

Model	S1212-ACE	S1212-HAE	S1212-ACE+	S1212-PACE
Dimension				
Max. Working Height (Indoor) *CE,ANSI A	13.80m 45ft 3in	13.80m 45ft 3in	13.80m 45ft 3in	13.80m 45ft 3in
Max. Working Height (Outdoor) *ANSI	11.20m 36ft 9in	11.20m 36ft 9in	11.20m 36ft 9in	10.00m 32ft 10in
Max. Platform Height (Indoor) *CE,ANSI B	11.80m 38ft 9in	11.80m 38ft 9in	11.80m 38ft 9in	11.80m 38ft 9in
Max. Platform Height (Outdoor) *ANSI	9.20m 30ft 2in	9.20m 30ft 2in	9.20m 30ft 2in	8.00m 26ft 3in
Overall Length C	2.48m 8ft 2in	2.48m 8ft 2in	2.48m 8ft 2in	2.48m 8ft 2in
Overall Width D	1.19m 3ft 11in	1.19m 3ft 11in	1.19m 3ft 11in	1.19m 3ft 11in
Overall Height(Rails Up) E	2.62m 8ft 7in	2.62m 8ft 7in	2.62m 8ft 7in	2.62m 8ft 7in
Overall Height(Rails Down) F	2.09m 6ft 10in	2.09m 6ft 10in	2.09m 6ft 10in	2.09m 6ft 10in
Platform Size(L×W)	2.27m×1.12m 7ft 5in×3ft 8in	2.27m×1.12m 7ft 5in×3ft 8in	2.27m×1.12m 7ft 5in×3ft 8in	2.27m×1.12m 7ft 5in×3ft 8in
Platform Extension Size G	0.90m 2ft 11in	0.90m 2ft 11in	0.90m 2ft 11in	0.90m 2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m 4in/1in	0.10m/0.019m 4in/1in	0.10m/0.019m 4in/1in	0.10m/0.019m 4in/1in
Wheelbase H	1.87m 6ft 2in	1.87m 6ft 2in	1.87m 6ft 2in	1.87m 6ft 2in
Turning Radius(Inside/Outside)	0m/2.20m 0in/7ft 3in	0m/2.20m 0in/7ft 3in	0m/2.10m 0in/6ft 11in	0m/2.20m 0in/7ft 3in
Tyres	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm
Performance				
S.W.L *CE	320kg 705lb	320kg 705lb	350kg 772lb	320kg 705lb
S.W.L *ANSI	318kg 701lb	318kg 701lb	350kg 772lb	320kg 705lb
S.W.L On Extension	113kg 249lb	113kg 249lb	113kg 249lb	113kg 249lb
Max. Occupants (Indoor/Outdoor) *CE	3/0	3/0	3/0	2/0
Max. Occupants (Indoor/Outdoor) *ANSI	2/1	2/1	2/1	2/1
Gradeability	25%	25%	25%	25%
Travel Speed(Stowed)	5.0km/h 3.10mph	3.5km/h 2.17mph	6.0km/h 3.73mph	5.0km/h 3.10mph
Travel Speed(Raised)	0.8km/h 0.50mph	0.8km/h 0.50mph	0.8km/h 0.50mph	0.8km/h 0.50mph
Max. Working Slope	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°
Up/Down Speed	55/40sec	58/40sec	52/52sec	55/55sec
Weight				
Overall Weight *CE	2990kg 6591lb	2980kg 6569lb	3210kg 7077lb	3200kg 7055lb
Overall Weight *ANSI	3210kg 7077lb	3200kg 7055lb	3210kg 7077lb	3200kg 7055lb
Power				
Hydraulic Tank	20L 5.3gal	20L 5.3gal	20L 5.3gal	/
Lead-Acid Maintenance-Free Battery	24V/240Ah	24V/240Ah	/	24V/240Ah
Lithium Battery	24V/220Ah	24V/220Ah	28.8V/175Ah	/
Charger	24V/30A	24V/30A	28V/30A	24V/30A
Driving Motor	2×15VAC/0.87kW	/	2×15VAC/0.87kW	2×15VAC/0.87kW
Lifting Motor	15VAC/3.5kW	15VAC/3.5kW	15VAC/3.42kW	24VDC/1.8kW