

241CFM DIESEL AIR COMPRESSOR PORTABLE (7BAR)

**XAS
138**

**1 COMPRESSOR
TO COVER
MUTIPLE
APPLICATIONS**

**3 YOU CAN
POWER 3 TOOLS
WITH EASE**
(ALONG WITH A NUMBER OF
OTHER APPLICATIONS)

**8 GREAT
REASONS TO
MAKE THE
INVESTMENT**

Atlas Copco



Model		XAS 138	XAHS 108
Normal effective working pressure	bar	7	12
Normal effective working pressure	psig	100	175
Actual free air delivery	m ³ /min	7	5,5
	cfm	250	189
	l/s	117	89
Max. sound pressure level	dB(A)	98	98
Max. ambient temp	°C	45	45
Min. starting temperature	°C	-10	-10
Min. starting temp (cold start)	°C	-20	-20
Engine		Kubota V2403-M-DI-TE2B	Kubota V2403-M-DI-TE2B
Emission stage		Stage II / Tier 2	Stage II / Tier 2
Engine power	KW	47,9	47,9
Full load	rpm	2700	2700
Unload	rpm	1800	1800
Engine oil	l	9,5	9,5
Compressor oil	l	11	11
Fuel tank	l	87	87
Dimensions			
Length (inc. fixed tow bar)	mm	3747	3747
Width	mm	1593	1593
Height	mm	1572	1572
Weight	kg	1300	1300