HAC60K3-50 GENERATOR

60KVA HYBRID GENERATOR HYBRID AC

Globe Power's Lithium Iron Phosphate Hybrid AC units provide a reduction of diesel consumption and are low emission, assisting in reducing carbon footprint and hitting green energy emission targets.

Suitable for a high load start up and low running power demands, the all in one system is both efficient in power and cost.

AUSTRALIAN DESIGNED | SMART FEATURES & LATEST TECHNOLOGIES | DURABLE & COST EFFECTIVE | EASY TO TRANSPORT



Powered By: SOLAR TECH GROUP



PRODUCT SPECIFICATIONS

GENERAL

Model	HAC60k3-50
Voltage	400V 3 phase AC 50Hz
Output Power	60kVA continous load, standby peak 95kVA (1hr)

BATTERY

Battery Type	48V Lithium Iron Phosphate
Battery Capacity	51.2kWh
Recharge Time	3 hours (10-100%)

OPERATIONAL DATA

Operating Temperature	0°C - 50°C
Altitude	0 - 1500m
IP Rating	IP54
Input	32A 3 phase input for charging
Output	2x15A, 2x32A, 1x63A, IP66 outlets, 400A quick connects

UNIT

Dimensions (LxWxH)	2880 x 1420 x 2760
Weight (WET)	3,800kg
Engine	Deutz BF4M2012 (Tier 5 Engine Available)
Cooling	6 x Air Conditioner
Fire Prevention	4.5kg ABC Extinguisher & Battery fire suppression modules

FUEL CONSUMPTION

Fuel Consumption (L/h)	10.6L @ 75% Load
Fuel Tank Capacity (L)	360L - 110% Bunded
	includes 3 way fuel valves

NOISE LEVEL

Sound Pressure	73db @ 7m

SOLAR INPUT

Voltage	250V DC Max
Power	4 x 4kW Charge Controllers
	Suits up to 8 Solar Skids

GP-HAC60K3-50-V3-0525

Disclaimer: Specifications are indicative only and may vary between model years or individual units. For equipment hire, we will supply the same or an equivalent model that is fit for the disclosed purpose.