

XAS68D AIR COMPRESSOR

135CFM DIESEL AIR COMPRESSOR PORTABLE (7BAR)

Performance		XAS 38	XAS 48	XAHS 38	XAS 58	XAS 68
Working pressure	bar (g)	7	7	12	7	7
	psi (g)	100	100	175	100	100
Max. free air delivery	m ³ /min	2	2,5	2,3	3	3,5
	cfm	70	90 (108*)	81	106	125
Output power	kVA	-	-	-	-	-
Max. ambient temperature at sea level	°C	50	47 (43*)	50	50	50
Min. starting temperature / (cold start Aid)	°C	-10 / -20	-10 / -20	-10 / -20	-10 / -20	-10 / -20
Engine						
Model		KUBOTA D 722	KUBOTA D 902	KUBOTA V 1505	KUBOTA V 1505	KUBOTA V 1505
Number of cylinders		3	3	4	4	4
Power output @ normal shaft speed	kW	14,9	18,5	26,5	26,5	26,5
Nominal speed	rpm	3400	3400 (3600*)	3000	3000	3000
Unload speed	rpm	2000	2000 (2200*)	1800	1850	1850
Capacity						
Engine oil	l	3,8	3,8	5,5	5,5	5,5
Compressor oil	l	6	6	8	8	8
Fuel tank capacity	l	28,5	28,5	60	60	60
Noise level						
Sound power level (LwA)	dB(A)	97	98 (99*)	98	98	98
Sound pressure level (LpA) at 7m	dB(A)	70	70 (71*)	70	70	70
Dimensions and weight (box unit / undercarriage)						
Length	mm	1570 / 1960	1570 / 1960	1940 / 2290	1940 / 2290	1940 / 2290
Width	mm	1060 / 1230	1060 / 1230	1180 / 1350	1180 / 1350	1180 / 1350
Height	mm	990 / 1250	990 / 1250	1150 / 1400	1150 / 1400	1150 / 1400
Weight (box/portable)	kg	440 / 500	440 / 500	650 / 749	650 / 749	650 / 749

*Values in brackets for non-European models

AVAILABLE OPTIONS INCLUDE:

- Adjustable towbar with brakes
- Adjustable towbar without brakes
- Fixed towbar with brakes
- Fixed towbar without brakes
- DoT approved undercarriage
- Support mounted
- Support leg
- Jockey wheel
- Road signalization + wheel chocks
- Towing eye (DIN, NATO, AC, ITA, GB, Ball coupling)
- Loose ball coupling
- Special colours
- Cold start
- Toolbox
- Aftercooler + water separator
- Aftercooler + water separator + reheater
- Aftercooler by-pass
- Additional fuel filter
- Safety cartridge (standard on XAS 38 and XAS 48)
- Lubricator
- Non-return valve
- Hose reel
- LED lights
- Refinery equipment (XAHS 38 and up)

