XAS68D AIR COMPRESSOR

130CFM DIESEL AIR COMPRESSOR PORTABLE (7BAR)

Performance		XAS 38	XAS 48	XAHS 38	XAS 58	XAS 68
Working pressure	bar (g)	7	7	12	7	7
	psi (g)	100	100	175	100	100
Max. free air delivery	m³/min	2	2,5	2,3	3	3,5
	cfm	70	90 (108*)	81	106	125
Output power	kVA	-	-	-	-	-
Max. ambient temperature at sea level	°C	50	47 (43*)	50	50	50
Min. starting temperature / (cold start Aid)	°C	-10 / -20	-10 / -20	-10 / -20	-10 / -20	-10 / -20
Engine						
Model		KUBOTA D 722	KUBOTA D 902	KUBOTA V 1505	KUBOTA V 1505	KUBOTA V 1505
Number of cylinders		3	3	4	4	4
Power output @ normal shaft speed	kW	14,9	18,5	26,5	26,5	26,5
Nominal speed	rpm	3400	3400 (3600*)	3000	3000	3000
Unload speed	rpm	2000	2000 (2200*)	1800	1850	1850
Capacity						
Engine oil	l	3,8	3,8	5,5	5,5	5,5
Compressor oil	l	6	6	8	8	8
Fuel tank capacity	l	28,5	28,5	60	60	60
Noise level						
Sound power level (LwA)	dB(A)	97	98 (99*)	98	98	98
Sound pressure level (LpA) at 7m	dB(A)	70	70 (71*)	70	70	70
Dimensions and weight (box unit / undercarriage)						
Length	mm	1570 / 1960	1570 / 1960	1940 / 2290	1940 / 2290	1940 / 2290
Width	mm	1060 / 1230	1060 / 1230	1180 / 1350	1180 / 1350	1180 / 1350
Height	mm	990 / 1250	990 / 1250	1150 / 1400	1150 / 1400	1150 / 1400
Weight (box/portable)	kg	440 / 500	440 / 500	650 / 749	650 / 749	650 / 749

*Values in brackets for non-European models

AVAILABLE OPTIONS INCLUDE:

- Adjustable towbar with brakes
- Adjustable towbar without brakes
- Fixed towbar with brakes
- Fixed towbar without brakes
- DoT approved undercarriage
- Support mounted
- Support leg
- Jockey wheel
- Road signalization + wheel chocks
- Towing eye (DIN, NATO, AC, ITA, GB , Ball coupling)
- Loose ball coupling
- Special colours
- Cold start
- Toolbox
- Aftercooler + water separator
- Aftercooler + water separator + reheater
- Aftercooler by-pass
- Additional fuel filter
- Safety cartridge (standard on XAS 38 and XAS 48)
- Lubricator
- Non-return valve
- Hose reel
- LED lights
- Refinery equipment (XAHS 38 and up)



Disclaimer: Specifications are indicative only and may vary between model years or individual units. For equipment hire, we will supply the same or an equivalent model that is fit for the disclosed purpose.