

P27.6AU PLUS TELEHANDLER

2.7T DIESEL TELEHANDLER INDUSTRIAL (6.0M)

PERFORMANCE			
Total unladen weight (kg)	4850		
Maximum capacity (kg)	2500		
Lifting height (m)	5,9		
Maximum reach (m)	3,3		
Maximum operating height (m)	4,5		
Maximum operating reach (m)	1,2		
Capacity at maximum height (kg)	1500		
Capacity at maximum reach (kg)	900		
Lateral boom movement (mm)	-		
Tilting correction (%)	-		
Boom sections	2		
POWERTRAIN			
Turbo motor	Kohler KD2504 TCR		
Displacement/cylinders	2500/4		
Engine Power (kW/HP)	55,4/75,1		
Anti-pollution technology	TIER 4F, STAGE IV, DOC		
Reversible fan	-		
Maximum speed (km/h)	40		
Fuel tank (l)	70		
AdBlue tank (l)	-		
Hydrostatic transmission	● - 1V		
EPD	-		
Axles	Axial		
Reduction hub	Epicyclic		
Machine brakes	Dry disc		
Automatic parking brake	●		
HYDRAULIC			
Hydraulic pump	Gear		
Flow rate/pressure (l/min - bar)	95-210		
Hydraulic tank	70		
Hydraulic outlet at the top of the boom	●		
Rear hydraulic outlets	○		
CAB			
Cab configuration	ECO		
MCDC	-		
FOPS L/V II cab	●		
ROPS cab	●		
Cab commands	Electromechanic joystick		
Tilting Cab	-		
Reverse shuttle	Finger touch		
CONFIGURATION			
Cab suspension	-		
Boom suspension	●		
Suspension on axles	-		
Work headlights on cab	●		
Sun blind	●		
Tac-lock	●		
Provision for a platform	○		
Two floating forks	●		
Inching-Control	●		
Four-wheel drive	●		
Four-wheel steering	●		
Three steering modes	●		
Standard tyres	12.0/75-18"		
Optional tyres	-		
Stabilisers	-		
Turret rotation	-		
Type approval as an agricultural tractor	-		
Approval with PNEUMATIC braking	-		
Approval with HYDRAULIC braking	-		
PTO	-		
3-point linkage	-		