

S0808-HAE SCISSOR LIFT

26FT ELECTRIC SCISSOR LIFT NARROW

Size	Metric	British
Max. Working Height A	10.00m	32ft 10in
Max. Platform Height B	8.00m	26ft 3in
Overall Length C	2.48m	8ft 2in
Overall Width D	0.83m	2ft 9in
Overall Height(Rails Up) E	2.36m	7ft 9in
Overall Height(Rails Down) F	2.00m	6ft 7in
Platform Size(Length×Width)	2.27m×0.81m	7ft 5in×2ft 8in
Platform Extension Size G	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m	4in/1in
Wheelbase H	1.87m	6ft 2in
Turning Radius(Inside/Outside)	0m/2.10m	0in/6ft 11in
Tyres	φ381×127mm	φ381×127mm

Performance

S.W.L	230kg	507lb
S.W.L On Extension	113kg	249lb
Max. Occupants (Indoor/Outdoor)	2/0	2/0
Gradeability	25%	25%
Travel Speed(Stowed)	3.5km/h	2.17mph
Travel Speed(Raised)	0.8km/h	0.50mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	30/34sec	30/34sec

Weight

Overall Weight	2210kg	4872lb
----------------	--------	--------

Power

Hydraulic Tank	20L	5.3gal
Lead-acid Battery	24V/185Ah	24V/185Ah
Lithium Battery	24V/180Ah	24V/180Ah
Charger	24V/30A	24V/30A
Lifting Motor	16VAC/3.5kW	16VAC/3.5kW

