

S0808-ACE+ SCISSOR LIFT

26FT ELECTRIC SCISSOR LIFT NARROW

Dimension	Metric	British
Max. Working Height(Indoor) A	10.00m	32ft 10in
★ Max. Working Height(Outdoor)	8.10m	26ft 7in
Max. Platform Height(Indoor) B	8.00m	26ft 3in
★ Max. Platform Height(Outdoor)	6.10m	20ft
Overall Length C	2.48m	8ft 2in
Overall Width D	0.83m	2ft 9in
Overall Height(Rails Up) E	2.36m	7ft 9in
Overall Height(Rails Down) F	1.90m	6ft 3in
Platform Size(Length x Width)	2.27m x 0.81m	7ft 5in x 2ft 8in
Platform Extension Size G	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m	4in/1in
Wheelbase H	1.87m	6ft 2in
Turning Radius(Inside/Outside)	0m/2.10m	0in/6ft 11in
Tyres	φ381 x 127mm	φ381 x 127mm

Performance		
S.W.L	272kg	600lb
S.W.L on Extension	113kg	249lb
Max. Occupants (Indoor/Outdoor)	2/0	2/0
★ Max. Occupants (Indoor/Outdoor)	2/1	2/1
Gradeability	25%	25%
Travel Speed(Stowed)	6.0km/h	373mph
Travel Speed(Raised)	0.8km/h	0.50mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	32/34sec	32/34sec

Weight		
Overall Weight(AGM Battery)	2325kg	5126lb
Overall Weight(Lithium Battery)	2230kg	4917lb

Power		
Hydraulic Tank	20L	5.3gal
AGM Battery	24V/185Ah	24V/185Ah
Lithium Battery	28.8V/150Ah	28.8V/150Ah
Charger	28V/30A	28V/30A
Driving Motor	2 x 15VAC/0.87kW	2 x 15VAC/0.87kW
Lifting Motor	15VAC/3.42kW	15VAC/3.42kW

Note: Parameters with "★" are optional

