SPT032-8X5-QLD TRAILER

3.2T PLANT TRAILER



DROP-DOWN RAMPS
Heavy-duty rear loading ramps for easier machinery loading.

FULLY WELDED DESIGN
Fully welded, hot-dipped galvanised construction with reinforced chassis and hinges.

3200KG ATM
3200kg Aggregate Trailer Mass rating with a confirmed tare weight of 590kg.

TANDEM AXLE
Heavy-duty greasable rocker roller suspension with electric brakes on all four wheels.

8x5 TRAILER DECK
Heavy-duty mesh floor with 2420 × 1510mm internal dimensions.

HEAVY-DUTY CONSTRUCTION
Reinforced chassis with heavy-duty 7-leaf springs for demanding applications.

SPECIFICATION	DETAILS
ATM	3200 kg
Tare Weight	590 kg
Internal Size	2420 x 1510 mm
External Size	4800 x 2100 mm
Drawbar	1900 mm: 100 x 50 x 4 mm
Chassis	100 × 50 × 3.0 mm Tube
Finish	Hot Dipped Galvanised
Side	220 mm High Steel Frame
Floor	Heavy Duty Mesh Floor
Jockey Wheel	8″ Steel Rim Swing Up
Wheels and Tyres	Brand New 15″ 195/R15LT Light Truck; Sunraysia Style with 6 Studs Pattern
Axle	50 x 50 mm Square Solid With Heavy Duty Parallel Bearings
Suspension	Heavy Duty Greasable Rocker Roller Suspension
Spring	Heavy Duty 7 Leaf Eye to Eye Spring
Coupling	50mm ADR Approved Australia Standard with Grease Nipples
Connection Plug	Round or Flat 7 Pin Plug
Safety Chain	13 mm
Brake	Electric Brakes on All 4 Wheels with Breakaway Unit
Lights	LED Set

SP-8X5PT-V1-1026

Disclaimer: Specifications are indicative only and may vary between model years or individual units. For equipment hire, we will supply the same or an equivalent model that is fit for the disclosed purpose. For capital sales, exact specification sheets will be provided upon a formal quotation