


TF35.7-140 TELEHANDLER

3.5T DIESEL TELEHANDLER INDUSTRIAL (7M)



MODEL	TF35.7CS-140	TF35.7-140
A - Length (in)	170	170
C - Wheelbase (in)	108	108
F - Ground clearance (in)	15	15
H - Width (in)	89	89
M - Cab width (in)	40	40
P - Height (in)	91	91
S - Fork steering range (in)	187	187

TF35.7-140 TELEHANDLER

3.5T DIESEL TELEHANDLER INDUSTRIAL (7M)

MODEL	TF35.7CS-140	TF35.7-140
PERFORMANCE		
Unladen weight (lb)	15322	15322
Maximum load capacity (lb)	7700	7700
Lift height (ft)	21'	21'
Maximum reach (ft)	11'	11'
Boom side-shift (in)	—	—
Frame levelling (%)	—	—
Boom section	2	2
POWERTRAIN		
Engine	DEUTZ TCD3.6	DEUTZ TCD3.6
Range/Cylinders (l)	3.6/4	3.6/4
Engine power (kW/HP)	100/136	100/136
Anti-pollution technology	Stage V • SCR • DGC • DPF	Stage V • SCR • DGC • DPF
Reversible Fan	●	●
Maximum speed (mph)	25	25
Fuel tank capacity (gal)	22.5	22.5
AdBlue tank capacity (gal)	3.2	3.2
Hydrostatic transmission EPO	●	●
Electronic joystick	STD	STD
Axes	Axial	Axial
Brakes	Dry discs	Dry discs
HYDRAULIC		
Delivery / pressure (gal/min-psi)	33-3048	33-3048
Hydraulic oil tank capacity (gal)	22.5	22.5
CAB		
ASCS	Light	Light
FOPS/ROPS Cab	●	●
Tilting cab	—	—
CONFIGURATION		
Hydropneumatic Suspension CS Merlo	●	—
Frame suspension	—	—
Permanent four-wheel drive	●	●
Three steering way	●	●
Standard tyres	400/70 - 24	400/70-24"
Hydraulically controlled stabilizers	—	—
Turnst rotation	—	—
PTO (rpm)	—	—
3-point rear linkage (lb)	—	—