

S70 LOADER

1.3T DIESEL LOADER

Model	S70	S450	S510	S590	S650
Loader Series	K-Series	M3-Series	M3-Series	M3-Series	M3-Series
Rated Operating Capacity (ROC) (35% of tipping load)	--	--	--	--	--
ROC (50% of tipping load)	760 lb. (344 kg)	1370 lb. (621 kg)	1876 lb. (851 kg)	2000 lb. (907 kg)	2690 lb. (1220 kg)
ROC With (optional 200 lb., 90 kg) Counterweight	--	1430 lb. (649 kg)	2023 lb. (917 kg)	2150 lb. (975 kg)	2840 lb. (1288 kg)
Tipping Load	1520 lb. (689 kg)	2740 lb. (1243 kg)	3754 lb. (1702 kg)	4202 lb. (1906 kg)	5380 lb. (2440 kg)
Height to Bucket Hinge Pin	94.5 in. (2400 mm)	109.5 in. (2781 mm)	114.5 in. (2908 mm)	119.0 in. (3023 mm)	124.0 in. (3149 mm)
Lift Arm Path	Radius	Radius	Radius	Vertical	Vertical
Size and Speed					
Operating Weight	2892 lb. (1312 kg)	5370 lb. (2436 kg)	6208 lb. (2816 kg)	6765 lb. (3069 kg)	8061 lb. (3656 kg)
Width With Bucket	36.0 in. (914 mm)	62.0 in. (1575 mm)	68.0 in. (1727 mm)	68.0 in. (1727 mm)	74.0 in. (1880 mm)
Height With Cab	71.4 in. (1814 mm)	77.8 in. (1976 mm)	77.8 in. (1976 mm)	77.8 in. (1976 mm)	81.3 in. (2065 mm)
Travel Speed - Low Range	6.3 mph (10.1 km/hr.)	7.6 mph (12.3 km/hr.)	7.6 mph (12.3 km/hr.)	7.0 mph (11.2 km/hr.)	7.1 mph (11.4 km/hr.)
Travel Speed - High Range (optional 2-Speed travel)	--	9.2 mph (14.8 km/hr.)	11.0 mph (17.3 km/hr.)	11.4 mph (18.4 km/hr.)	12.3 mph (19.7 km/hr.)
Engine	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
Horsepower	23.5 hp (17.5 kW)	49.0 hp (36.5 kW)	55.0 hp (41.0 kW)	68.0 hp (50.7 kW)	74.0 hp (55.1 kW)
Type	Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel
Fuel Tank Capacity	6.5 gal. (24.6 L)	14.2 gal. (53.8 L)	24.8 gal. (93.7 L)	24.8 gal. (93.7 L)	23.9 gal. (90.5 L)
Horsepower Management	--	Included with SJC Option	Included with SJC Option	Included with SJC Option	Included with SJC Option
Tires					
Bobcat Heavy Duty	--	Std	Std	--	Std
Bobcat Standard Duty	Std	--	--	--	Opt (Parts)
Bobcat Superfloat Duty	--	--	--	Std	Opt (Parts)
Tracks/Undercarriage					
Track Width - Standard	--	--	--	--	--
Track Width - Optional	--	--	--	--	--
Ground Pressure (with standard tracks)	--	--	--	--	--
Ground Pressure (with optional tracks)	--	--	--	--	--
Length of Track on Ground	--	--	--	--	--
5-Link Torsion Suspension Undercarriage	--	--	--	--	--
Grease Cylinder Track Tensioning	--	--	--	--	--
Control Options					
Bobcat Standard (foot pedals/steering levers)	Std	Std	Std	Std	Std
Selectable Joystick Controls (SJC)	--	Opt	Opt	Opt	Opt
Radio Remote Control (SJC required)	--	Opt	Opt	Opt	Opt
Machine Features					
2-Speed Travel	--	Opt	--	Opt	Opt
Automatic Ride Control	--	--	--	Opt	Opt
Back-Up Alarm and Horn	Std	Std	Std	Std	Std
Bobcat Interlock Control System (BICS™)	Std	Std	Std	Std	Std
Cab With Heat	--	--	--	--	--
Cab With Heat and Air Conditioning	--	Opt	Opt	Opt	Opt
Heated Cloth Air-Ride Seat	--	--	--	--	Opt (Parts)
Hydraulic Bucket Positioning	--	--	--	Opt	Opt
Front and Rear Work Lights	Std	Std	Std	Std	Std
Mechanical Suspension Seat	Std	Std	Std	Std	Std
Radio	--	--	--	--	Opt (Parts)
Reversing Fan	--	--	--	--	Opt (Parts)
ROPS/FOPS Approved Cab Structure	Std	Std	Std	Std	Std
Deluxe Panel	--	Opt	--	--	--
Side Lighting Kit	--	--	--	--	Opt
Sound Reduction Package	Opt	Opt	--	--	Opt
Features for Attachments					
Attachment Control	--	--	--	Opt	Opt
Bob-Tach Mounting System	Std	Std	Std	Std	Std
Power Bob-Tach System	--	Opt	--	Opt	Opt
Fingertip Auxiliary Hydraulics Control	--	Std	Std	Std	Std
Hydraulic System Pressure	3000 psi (20.6 MPa)	3300 psi (22.7 MPa)	3550 psi (24.4 MPa)	3550 psi (24.4 MPa)	3500 psi (24.1 MPa)
Hydraulic Standard Flow	9.8 gpm (37.1 L/min.)	16.7 gpm (63.2 L/min.)	17.1 gpm (64.7 L/min.)	17.1 gpm (64.7 L/min.)	23.0 gpm (87.0 L/min.)
Hydraulic High Flow	--	--	--	--	--
Pressure Release Hydraulic Quick Couplers	--	Std	Std	Std	Std
Speed Management	--	Included with SJC Option	Included with SJC Option	Included with SJC Option	Included with SJC Option

*Ask your Bobcat dealer about installing this option. | **Optional